



SPECIFICATION REQUEST FORM

ADB TRAILER AXLE - ASSEMBLED AXLE

For complete pricing and model information, please fill in this form completely and do one of the following:

1. Click **"SAVE"** button on page 3 to save a copy to your computer. Then attach and email the Saved PDF to specs@axnheavyduty.com.
2. Click **"PRINT"** to print a copy and Fax to (502) 361-2313

FOR AXN HEAVY DUTY USE ONLY	
TRAILER AXLE PART NUMBER:	
AXN CONTACT:	
AXN CONTACT EMAIL:	
AXN CONTACT PHONE:	

CUSTOMER TO COMPLETE APPLICABLE INFORMATION BELOW			
COMPANY NAME:		DATE:	
TELEPHONE:		FAX:	
CONTACT:		EMAIL:	
SPECIAL INSTRUCTIONS:			

TRAILER AXLE			
Spindle	Tapered	Parallel	
Axle Profile	Straight	6.25" Drop Center	8" Drop Center
Axle Track	71.50"	77.50"	Other (Specify):
Axle Diameter/Wall Thickness	5.0" Standard		
	0.5" (10mm)	0.625" (12mm)	0.75" (15mm)
	5.75" Big Diameter		
	0.335" (8mm)	0.5" (10mm)	0.625" (12mm)
Top Center Hole	Without	With	
Spindle Nut Type	N-Series(3-Piece-double nut & washer) Stemco Zip Torq		P-Series(Castle nut, washer & Cotter Pin)

BRAKES			
Brake Size & Type	Disc Brake - 22"	Disc Brake - 17" (Wabco Pan17 Only)	
Wheel-ends (type)	Wabco Disc Brake Pan 22-1 (P/N's 6402250320 & 6402250330) - Fuwa Hub & Rotor Only Bendix ADB22XA & ADB22XB Brake (P/N's 5014175 & 5014174) - Walther EMC Hub & Rotor		
Caliper	Bendix	Wabco (FUWA)	Haldex Other (Specify):
Rotor Shields	Without	With (Only Wabco , Pre-Installed)	
Brake Orientation	Calipers 270 Degrees Front, Actuator 45 Degrees Rear <small>"Calipers 90 Degrees Rear, Actuator Ports 45 Degrees Rear"</small> <small>"Caliper 270 Degrees Front / Port 45 Degrees Rear"</small> *Calipers 90 Degrees Rear, Actuator 45 Degrees Rear Other (Specify):		
*If used with a Mechanical Suspension, 100 Degrees Rear, Actuator 45 Degrees Rear is Recommended for Brake Chamber Clearance			

BRAKE CHAMBERS

Chamber Brand	Without	AXN Standard	Other (Specify):	
Chamber Type	Service/Spring:	24/24	20/24	Other (Specify);
	Service Only:	T20	T24	Other (Specify);
Instructions	Install	Ship Loose		
Wheel-End Options				
Stud Length	Short	Long		
Wheel Nuts	Full Set	2 Per Wheel End	Other:	
Lube Brand	Standard AXN	Other (Specify):		
Lube Type	SAE 80W/90 Oil	NGLI #2 Grease	Semi Fluid Grease	SAE 75W-90 Synthetic oil
Seal Brand	AXN Standard	Other (Specify):		
Bearing Brand	AXN Standard	Other (Specify):		
Hubcap Type	AXN Standard	Other (Specify):		
HubCap TEMPBOLT	Without	With		
Hub Alert	Without	With		
ABS Sensor	Without	Wabco Sensor	Other (Specify)	

TIRE INFLATION SYSTEM

Tire Inflation Brand	Without	AXN Standard	Other (Specify):	
MTIS/P.S.I. Specifications	Drill, tap air inlet hole and install metal pipe plug			
	Drill Location:	Top Center	Other (Specify):	
	Prep Only			
	Install Spindle Plugs & Stators (Supplied & Installed by AXN)			
	Additional Preparation (Specify):			
Hendrickson Tire Maax Specification	Drill, tap air inlet holes and install metal pipe plug			
	Three Hole Drill & Tap			
	Additional Preparation(Specify):			